



## Features

- \* The T-8000A remote paging console is connected with T-8000 through universal industrial standard CAT 5 for zone announcement or communication at a remote and different location from the control center.
- \* Each controller provides four RJ45 ports for the remote paging console.
- \* The CAT 5 wiring is not only featured of cost-effective, convenient layout, but also integration of RS 485 communication and audio transmission together.
- \* Extra DC 24V power supply
- \* Eight zone selector with state indication.
- \* Talk and all zone paging swift keys are provided.
- \* 2 and 4 tones chimes with selector and off switch.
- \* Volume controls are provided for chime and microphone.
- \* Full indications includes individual zone, all zone busy, paging, power, output level to provide a direct visualization.

## Specifications

<b>Model</b>	T-8000AE
<b>MIC</b>	Condenser Microphone
<b>Frequency Response</b>	50Hz~18KHz ( $\pm 2$ dB)
<b>S/N Ratio</b>	Better than 75dB
<b>THD</b>	Less than 0.1% at 1KHz,
<b>Signal Output</b>	0.775V/600 $\Omega$
<b>Mic Input</b>	5mV/600 $\Omega$
<b>Indication</b>	Individual zone, all zone busy, paging, power, output level indicators
<b>Protection</b>	DC+24V/2A, Revert fuse protection
<b>Power Supply</b>	DC 24V
<b>Power Consumption</b>	5W
<b>Weight</b>	2.5Kg
<b>Dimensions</b>	180x143x52mm