



## Features

- \* Standard wall-mounted design, black brushed aluminum panels, exquisite appearance, sophisticated technology, filling high-grade temperament.
- \* Equipment with embedded computer technology and DSP audio processing technology design. high-speed industrial-grade chips, start-up time of less than 1 second.
- \* Built-in single network hardware audio decoding module, support TCP/IP, UDP, IGMP (Multicast) protocol, transmit 16-bit audio signal as same as CD quality through network transmission.
- \* 2 line output, connect external power amplifier or active speakers.
- \* 1 channel 500W intelligent output power outlet, can remote management via Ethernet, support software programming pre-opening function.
- \* An IP address reset button, if you lose the IP address, can restore factory default.
- \* Support 1000 classes audio priority mute control.
- \* Support PSTN phone broadcasting, support SMS voice broadcast.
- \* Support mobile WIFI on demand, wireless remote control on demand.
- \* Support panel serial port expansion on demand, to achieve remote programming on demand, program selections, adjust the volume.
- \* Support server authorized to operate a unified management, unified configuration management user and password.
- \* Support at least three kinds of high security authorization IP configuration, the safety factor is much higher than the Web and other remote configuration.
- \* Support digital audio playback breakpoint passage of time, to ensure that the broadcast synchronization effect.
- \* Support DHCP, compatible routers, switches, bridges, gateways, Modem, Intelnet, 2G, 3G, 4G, multicast, unicast and other random network structure.
- \* Support the new configuration registered intelligent voice prompts.
- \* Support ESD protection, built-in network isolation mine processing circuit.
- \* 1 channel to download the PC serial port IP address, is used to modify the IP address of network decoding module.
- \* Digital products, expansion of convenience, without geographical restrictions, no additional room management equipment, total net free line construction design, easy to install.

## Description

Install in low voltage room, low voltage box or sentinel-controlled room, classrooms, guess rooms and other places, connect external power amplifier or active speakers.

## Specifications

<b>Model</b>	T-6708
<b>Network Input</b>	Standard RJ45 Input
<b>Communication Protocol</b>	TCP/IP, UDP, IGMP (multicast)
<b>Audio Mode</b>	Mp3
<b>Sampling Rate</b>	8K~48KHz
<b>Transfer Rate</b>	100Mbps
<b>Audio Mode</b>	16-bit CD sound quality
<b>Output Frequency</b>	80Hz~16KHz
<b>T.H.D</b>	≤ 0.3%
<b>S/N Ratio</b>	>70dB
<b>Audio Output Level</b>	1000mV industry standard press-line connecting terminals
<b>Audio Output Impedance</b>	470Ω
<b>Working Temp</b>	5°C~40°C
<b>Humidity</b>	20%~80% Relative humidity, without condensation
<b>Power Consumption</b>	≤ 8W
<b>Power Supply</b>	~220-240V 50/60Hz
<b>Dimensions</b>	187 x 139 x 60mm
<b>Weight</b>	1.36Kg

## Rear Panel

