**itC**

## Features

TS-W111 is a dual frequency WIFI access unit for indoor area WIFI system. It adopts latest 802.11ac solution, which can provide a safe and stable high-speed WIFI network. With ceiling-type design, it looks exquisitely beautiful and with low space occupancy rate and fits with the indoor area. In addition, this intelligent AP adopts PoE power supply for easier installation and operation.

## Features

* Network throughput: it adopts 802.11n and 802.11ac as dual frequency and dual spatial flows technology to provide maximum 1.2Gbps kilo-mega WIFI access, providing indoor huge capacity and high throughput operation needs.
* Flexible configuration: Under different network bandwidth, you can adopt different configuration methods in different disposition. Under low bandwidth,  bandwidth network, it can deploy independently flexibly. Under high bandwidth network, it can operate with WIFI network controller to realize centralized management control with improved operating stability.
* WIFI security: WIFI AP supports multiple certificated encrypted standards including OPEN, WEP, WPA, WPA2, WPA-PSK, WPA2-PSK, 802.11i, and it provides certifications of MAC, WEB, 802.1x, fishing AP testing, WIFI user isolation and security feature of WIFI user blacklist and whitelist. It helps provide a safe network environment to the user.

## Specifications

| Model | TS-W111 |
|---|---|
| Power supply/Installation | POE(IEEE 802.3at) |
| Installation method | ceiling, desktop, wall mounted |
| Consumption | Average power consumption 11W/Peak power consumption 20W |
| Measurement | 180mm ×60mm |
| Weight | 0.27Kg |
| Connected delegate qty | 55 pieces |