



## Features

- \* Unique patented technology, specially designed anti-RF radio frequency interference tube, which can completely eliminate the noise, Showing a perfect high-level conference environment.
- \* Unique patented design, Fully embodies the designer to grasp the vision of the world aesthetics.
- \* Unique microphone head design, So that even if the speaker does not have the cotton cover, but also completely eliminate the "pupu" low-frequency impact.
- \* Professional heart-shaped condenser microphone core, Very high sensitivity and voice clarity; And with a ring of red & green indicator light when speaking.
- \* When the red ring light is on, it means somebody is speaking; when green is on, it means apply for awaiting speech.
- \* It has function of suppress whistle, when microphone is open, the built-in speaker will be closed automatically.
- \* Built-in speaker, headset jack, which can adjust the headset volume.
- \* Use the professional 8 core aviation plug by cascading units, and with the metal fixed nut to avoid loosing and falling.
- \* It has 1.8m 8 core connection line that is used full line of aluminum foil and waterline shield, which greatly reduce the interference of strong electromagnetic waves on the wire, avoid "zizi" noise.
- \* The address code of each unit can be adjusted at any time to facilitate the construction.
- \* It is passive equipment, which is powered by the system controller, input voltage is 24V, belongs to the safe scope.
- \* Chairman unit has no limited by speakers qty.
- \* Chairman unit has priority function of taking full control of the order of the meeting, can approve or reject the application for a delegate unit.
- \* The Chairman unit connection position is not limited; can be connected in any position of circuit.
- \* "Hand-in-hand" Cable cascade mode, which is easy to install and maintain.
- \* There are 5 multi-functional buttons for voting, election and meeting evaluation.
- \* The button indicator has a prompt for real-time voting.
- \* Speaking unit can apply or cancel to speak;
- \* LCD display can show the operation of the vote, voting mode, to avoid mistakes.

## Specifications

Model	TS-0622
Microphone Type	Heart-oriented directional electret
Frequency Response	80Hz~16KHz
Microphone Input Impedance	1KΩ
Sensitivity	-46 dBV/Pa
Max SPL	100dB(THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Power Consumption	2.5W
Headphone Load	8-32Ω
Headphone Volume	Max 40mW
Headphone Interface	3.5mm Headphone monaural jack
Follow Standard	IEC60914
Connector	1.8m aviation 8 core cable
Hand-in-hand Expansion Port	Unavailable
Power Supply Mode	Controller power supply DC24V
Voting Function	5/3 keys to vote
Sign-in Function	Button sign-in
Color	Silver
Display	Chinese and English font full dot matrix LCD display
Weight	0.9kg
Display Screen	LCD blue screen blue on white
Microphone Height	460mm
Dimension(mm)	225(L)×131(W)×48(H)
Installation Method	Tabletop